

852 Mountain Hwy, Bayswater VIC 3153 Telephone (03) 9720 7266 Facsimile (03) 9720 7191 karemwoodcraft@bigpond.com www.karemwoodcraft.com.au

Phone No: (0)

HOW TO MEASURE WINDOW PELMETS

Store:

Contact:

 Measure width of the curtain rails and add clearance (C) to calculate the TOTAL INTERNAL WIDTH (W) of the Pelmet.

We recommend a clearance of 50 mm each side to find out the total internal width of the Pelmet.

- Measure the distance from the front curtain to the wall plus clearance (so curtain doesn't rub on the back of the pelmet) to find the Internal Hanging Space (H). Pelmet Standard H sizes are 150 mm and 200 mm.
- Using the form bellow, provide the internal width (W) and internal hanging space (H) with clearance included.



NOTE: Pelmets must be wider than the curtain tracks and the window to allow full view of the window when curtains are opened. Eg. If window is 900 mm wide, allow 200 mm onto the width of the pelmet which would be then 1100 mm wide <u>internally</u>.

When ordering, all measurements supplied must be INTERNAL MEASUREMENTS with all clearances included

EXAMPLE:		150 and 200 mm
	WP Quantity: <u>1</u> Internal Width (W): <u>1810</u> mm Distance (D): <u>20</u>	
MATERIAL:	Thickness: <u>12</u> mm [MDF] LOSP T / PINE or OTHER_	
TO ORDER, FILL IN BELOW		
CODE:	Quantity: Internal Width (W): mm Distance (D):	mm
MATERIAL:	Thickness: mmMDFLOSP T / PINE or OTHER	
Please note that it is your responsibility to check all sizes are correct.		

Fax No. (0)